



# **Flexible** Reliable **Affordable**

















## **Increased productivity**

Offers a wide range of paper handling options to satisfy the varying needs of users.





## **Department codes**

Administrators can manage printing cost by tracking the print volume of departments and users, limiting unauthorised usage through this simple security management.



## **Duplex copying and printing**

Hassle-free copying and printing help reduce paper use significantly.



# **Colour Scan and Scan to USB**

Besides having the capability of Colour Scan, users can also enjoy the convenience of scanning directly to USB drive.



Specifications	e-STUDIO2006/2306/2506	e-STUDIO2007/2307/2507
General		
Copying/Printing Process	Indirect electrostatic photographic method	
Print & Copy Speed	20/23/25ppm	
Warm-up Time	Approx. 20 sec.	
Paper Size & Weight	Drawer: A3-A5R (64-80g/m²)	
Tapor oizo a troigiti	Stack Feed Bypass: A3/A5-R (52-163g/m²)	
Paper Capacity	Drawer: 250 sheets	
Рарег Сараску		
	Stack Feed Bypass: 100 sheets	
	Envelope (COM10, MONARCH, DL)	4900
Max. Paper Capacity	600 sheets	1700 sheets
Paper Exit	Face down/Inner exit (100 sheets)	
Processor	CortexA8 500MHz	
Memory	512MB (Shared)	
Dimensions	W575 x D540 x H402 (mm)	
Weight (Approx.)	25.5kg	
Power Consumption	1.5kW (220-240V)	
Operation Noise	64.4dB	
Special Features	Auto Sleep Mode, Auto Energy Saver	
	, and diddy mode, and Energy dates	
Сору		
Max. Original Size	A3	
Resolution	600 x 600dpi	
Multiple Copy Qty	1-999 (Ten key input)	
First Copy	Approx. 7.0 sec. (A4 size from 1st drawer, 100%)	
Zoom	25% to 400% (1% Increment)	
Copy Mode	Text, Text/Photo, Photo, Background Erase	
Image Density Control	Automatic/Manual (9 steps)	
	Automatic/Manual (9 steps)	
Print		
Resolution	600 x 600dpi, 2400 x 600dpi (With smoothing)	
Page Description Language	GDI	PCL6 (PCL XL)
Operating Systems	Windows XP/Windows Vista (32/64bit)	
	Windows 7/Windows 8 (32/64bit)	
	Windows 7/7/11/100/8/3 6 (32/64bit)	
	Windows Server 2012 (64bit)	
Interface	USB 2.0/Hi Speed	Standard: 10/100 BaseT, USB 2.0/Hi Speed
Network Protocol	N.A	TCP/IP (IP v4/IP v6)
		NetBIOS over TCP/IP
Print Protocol	N.A	LPR/LPD, Port 9100 (bi-directional), IPP ver1.0
Scan		
Decelution	600 v 600dpi	
Resolution	600 x 600dpi	
Scan Speed	Up to 25spm	
Scan Modes	B&W, Greyscale, Colour	
File Formats	B&W: TIFF-Multi/Single page, PDF-Multi/Single page	
	Greyscale & Colour: JPEG, TIFF-Multi/Single page, PDF-Multi/Single page	
Compatibility	TWAIN	
Scan Agent	N.A	Scan to USB, Remote TWAIN
		Scan to File (SMB/FTP), Scan to Email
FAX		
Compatibility	N,A	Super G3, G3
Compatibility		
Data Compression Method	N.A	JBIG, MMR, MR, MH
Modem Speed	N.A	33.6kbps to 2.4kbps (Automatic Fallback)
Transmission Speed	N.A	Approx. 3 sec.
Broadcast Transmission	N.A	Max. 220 destinations per job
Options		
MR-3027	Document Feeder (RADF)	
KA-2507PC	Platen Cover	
MY-1043	Paper Feed Unit	
KD-1039	N.A	Paper Feed Pedestal
MY-1044	N.A	Drawer Module
MD-0106	Auto Duplex Unit	
GD-1330	N.A	FAX Kit
GN-1080	N,A	Wireless LAN module
	Harness kit for coin controller	
GQ-1131	Harriess kit for controller	

## **Distributed by**

Microsoft and Windows® are registered trademarks of Microsoft Corporation in the United States and/or other countries.

Microsoft and vindows@ are registered trademarks of microsoft Corporation in the United States and/or other countries. This brochure was compiled based on information that was accurate prior to product launch. Product design and specifications are subject to change without notice. The colour(s) of the actual product may vary from the colour(s) shown in this brochure. No part of this material may be used or reproduced in any manner whatsoever without permission. Warm-up time and print speed may vary depending on the operating environment. @2011 TOSHBA TEC CORPORATION All rights reserved.

As an ENERGY STAR Partner TOSHIBA TEC CORPORATION has determined that this multifunction device model meets the ENERGY STAR guidelines for energy efficiency.

Information is correct at the point of printing.



