

Canon

Delighting You Always

**imageRUNNER
2425**

Small in Size, Not in Functions

**PERFECT FOR SMALL AND
MEDIUM BUSINESSES**

⌄ **25pages/minute multi-function device**

⌄ **Monochrome printing**

⌄ **17.78 cm (7 inch) colour touch panel**

⌄ **Optimal security**

⌄ **Flexible mobile support**



imageRUNNER 2425

Advanced functions made simple

Experience an entry level monochrome multi-function device that offers advanced features in a simplified body.

Boasting a range of comfortable operability and optimal security features, the new imageRUNNER 2425 is the perfect printing solution for small and medium businesses.



Wi-Fi Connect



Scan/ Copy



Mobile Support



Touch Panel



Optimal Security

Seamless Usability

Smooth operation with 17.78 cm (7-inch) colour UI.

The colour touch panel provides great visibility and functionality, displaying useful information at a glance. A full keyboard support allows for easy interaction and data input.

The user interface is similar to the imageRUNNER ADVANCE series, providing an unified user experience across our products.



9 STEPS INTO 1

Increase efficiency of routine work with a touch.

Customisable buttons provide endless personalisation in combining multiple operation settings into one, streamlining workflow and increasing convenience.

A timeline function provides quick reference to previously executed settings, reducing the need for repeated settings.



Security

Optimal Security

The imageRUNNER 2425 comes with a range of up-to-date security features to prevent information leakage or unauthorised access.

uniFLOW Online/ Online Express



uniFLOW Online Express provides improved security through authentication functions, limiting users and their usage as well as prevent scan destination errors.

Document Security



Documents can be held at the machine with **Force Hold Print** until the user releases the job, preventing information leakage from unattended documents.

Device Verification



Verify System at Start-up checks the validity of the device firmware and applications to prevent unauthorised modifications.



Connectivity

Flexible mobile support

The imageRUNNER 2425 supports a wide range of mobile applications such as Canon PRINT Business, AirPrint™, Mopria® and Canon Print Service.

Print or scan documents even without a computer or a router Wi-Fi connection by connecting directly to the multi-function device.



YOU CAN DOWNLOAD FROM
APP STORE OR GOOGLE PLAY



Easy Digitisation

Scan and print documents efficiently.

An integrated Scan Preview allows quick checks on scanned documents for errors before sending, saving time and reducing the need for rescan.

Scanned data are easily transferable to USB and data can be checked before printing to prevent misprints, speeding up workflow efficiency.

SPECIFICATION

MAIN UNIT	
Machine type	A3 Monochrome Laser Multifunctional
Core functions	Print, Copy, Scan, Send and Optional Fax
Control Panel	17.78 cm (7 inch) TFT LCD WVGA colour touch panel
Memory	Standard: 2.0GB RAM
Storage	eMMC: 30GB
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Others Standard: USB 2.0 (Host) x3, USB 2.0 (Device) x1
Paper Supply Capacity A4, 80g/m ² (gsm)	Standard: 330 sheets Maximum: 580 sheets (with Cassette Feeding Module-AK1)
Paper output capacity A4, 80g/m ² (gsm)	Standard: 250 sheets Maximum: 250 sheets
Supported media sizes	Multi-purpose tray: A3, A4, A4R, A5, A5R, B4, B5, B5R, Envelopes (No. 10(COM 10), Monarch, ISO-C5, DL) Custom Size/Free Size: Min. 95.0 x 139.7 mm up to 297.0 x 431.8 mm Paper Cassette: A3, A4, A4R, A5R, B4, B5, B5R
Supported media weights	Multi-purpose tray: 60 to 157 g/m ² (gsm) Paper Cassettes: 64 to 90 g/m ² (gsm) Duplex: 60 to 90 g/m ² (gsm)
Warm-up Time (Quick start mode: ON)	4 Seconds or Less* *Time from device power-on to when key operations can be performed on the touch panel display. From Sleep Mode: 10 seconds or less 12 Seconds or Less* *Time from device power on, until copy ready (not print reservation)
Dimensions (W x D x H)	With Platen Cover-AA1: 627 x 665 x 516 mm With DADF-AZ2: 627 x 692 x 616 mm
Installation Space (W x D)	1 065 x 1 285 mm
Weight	With Platen Cover-AA1: 34.9kg including toner With DADF-AZ2: 39.9kg including toner
PRINT SPECIFICATIONS	
Print Speed (BW)	Up to 25 pages/minute (A4), Up to 12 pages/minute (A3), Up to 11 pages/minute (A4R)
Print Resolution (dpi)	600 x 600
Page description languages	Standard: UFR II Optional: PCL6, Adobe®PostScript®3™
Direct Print	Supported file types: RUI: PDF, EPS, TIFF/JPEG, XPS USB Memory/Network Place: PDF, TIFF/JPEG, XPS
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T ¹ (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts ² PS fonts: 136 Roman ¹ Requires optional PCL International Font Set-A1 ² Requires optional Barcode Printing Kit-D1
Operating System	UFR II: Windows® 7/8.1/10/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, MAC OS X (10.10 or later) PCL: Windows® 7/8.1/10/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019 PS: Windows® 7/8.1/10/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, MAC OS X (10.10 or later) PPD: Windows® 7/8.1/10, MAC OS X (10.10 or later)
COPY SPECIFICATIONS	
Copy Speed (BW)	Up to 25 pages/minute (A4), Up to 12 pages/minute (A3), Up to 11 pages/minute (A4R)
First-Copy-Out Time (A4) (BW)	7.4 seconds or less
Copy resolution (dpi)	600 x 600
Multiple Copies	Up to 9 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100%, 115%, 122%, 141%, 200%, 400%
SCAN SPECIFICATIONS	
Type	Optional: Duplexing Automatic Document Feeder (2-sided to 2-sided) (DADF-AZ2) or Platen Cover (Platen Cover-AA1)
Document Feeder Paper Capacity 80 g/m ² (gsm)	DADF-AZ2: 50 Sheets
Acceptable originals and weights	Platen: Sheet, Book Document Feeder media weight: 1-sided scanning: 37 to 128 g/m ² (gsm) (BW/CL) 2-sided scanning: 52 to 128 g/m ² (gsm) (BW/CL) Only 1-sheet feeding is supported in 37-52 and 105-128 g/m ² (gsm).

SCAN SPECIFICATIONS	
Supported media sizes	Platen: max. scanning size: 297.0 x 432.0 mm Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R Custom size: 139.7 x 148.5 mm to 297.0 x 432.0 mm
Scan Speed (images/minute: BW/CL; A4)	DADF-AZ2: 1-sided Scanning: 35/25 (300 dpi, send), 25/13 (600 dpi, copy) 2-sided Scanning: 12/8 (300 dpi, send), 8/4 (600 dpi, copy)
Scan Resolution (dpi)	Scan for Copy: up to 600 x 600 Scan for Send: (Push/Pull, BW) up to 600 x 600 (Push/Pull, CL) up to 300 x 300 Scan for Fax: up to 600 x 600
Pull Scan Specifications	Color Network ScanGear2. For both TWAIN and WIA
Supported OS	Windows® 7/8.1/10 Windows® Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016
Scan Method	Push scan, Pull scan, Scan to Network, Scan to memory media (USB Memory Key), Scan to Mobile Devices, Scan to cloud-based services (uniFLOW)
SEND SPECIFICATIONS	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB3.0, FTP WebDAV Optional: Super G3 FAX
Address Book	LDAP (2 000)/Local (1 600)/One-touch (200)
Send resolution (dpi)	Push: 100 x 100, 150 x 150, 200 x 100 (Standard), 200 x 200 (Fine), 200 x 400*(SuperFine), 300 x 300, 400 x 400*(UltraFine), 600 x 600* Pull: 75 x 75, 100 x 100, 150 x 150, 200 x 200, 300 x 300, 400 x 400*, 600 x 600* *Only applicable for black and white, even if colour mode is selected.
Communication protocol	File: FTP (TCP/IP), SMB (TCP/IP), WebDAV Email/iFax: SMTP(send), POP3(receive)
File Format	Standard: TIFF (MMR), JPEG*, PDF (Compact, PDF/A-1b, Encrypted), XPS (Compact), PDF/XPS (Device Signature) Optional: PDF (Trace & Smooth), PDF/XPS (User Signature), PDF/XPS (Searchable), Office Open XML (PowerPoint, Word) *Single page only
FAX SPECIFICATIONS	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Receiving Size	Sending: A3, A4, A4R, A5 ² , A5R ² , B4, B5 ¹ , B5R ² Receiving: A3, A4, A4R, A5R, B4, B5, B5R ¹ Sent as B4 ² Sent as A4
FAX memory	Up to 30 000 pages
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes
ENVIRONMENTAL SPECIFICATIONS	
Power source	220-240V 50/60Hz 2.7A
Power consumption	Maximum: 1 500 W Standby: 22.1 W ¹ Sleep mode: 1 W ² , 2 W ³ ¹ Reference value: measured one unit ² Wireless LAN power save mode OFF ³ Wireless LAN power save mode ON ^{2/3} Sleep mode is not available in all circumstances due to certain settings.
CONSUMABLES	
Toner Cartridges	NPG-59 Black Toner
Toner Yield (Estimated Yield @ 6% coverage)	Black: 10 200 impressions (A4)
PAPER SUPPLY OPTIONS	
Cassette Feeding Module-AK1	Cassette Feeding Module-AK1 Paper Capacity: 250 sheets 80 g/m ² (gsm) Paper Type: Plain, Recycled, Colour, Pre-punched Paper Size: A3, A4, A4R, A5, B4, B5, B5R Paper Weight: 64 to 90 g/m ² (gsm) Power Source: Main Unit Dimensions (W x D x H): 581 x 575 x 92 mm Weight: 5.8kg
OTHER ACCESSORIES	
DADF-AZ2, Platen Cover-AA1, PCL International Font Set-A1, PS Printer Kit-CM1, PCL Printer Kit-CM1, Universal Send Digital User Signature Kit-C1, Universal Send Advanced Feature Set-H1, Barcode Printing Kit-D1, Copy Control Interface Kit-D1, Super G3 FAX Board-BE1, Remote Fax Kit-A1	

To arrange for a demonstration, simply contact:

CANON INDIA PVT. LTD.

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-416001 | Web: in.canon

This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document. Canon and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. Other names may be the trademarks for their respective owners.

All rights reserved. Printed in India.

